

HF 360 AP




Rapid-response, long-reach and versatile SensorSwitch using high-frequency technology. In the concealed version, ideal for stairwells, hallways and bathrooms, in the surface mounted version for stairwells, basements and laundries.

High-frequency detectors emit a no perceivable signal and respond to changes in the echo pattern caused by movement irrespective of temperature. With its generous detection range, virtually instant response behavior and a reach that can be infinitely varied between 1 m and 8 m, it is suitable even for difficult spaces.

- Splashproof, surface mounted high-frequency sensor, ideal for stairwells, basement stairs and indoor areas

Settings

- Control dials for easy adjustment of reach, light "ON" time and twilight threshold are protected from accidental maladjustment behind the screw-down trim panel.
- Integrated pushbutton for switching to permanent light "ON" (4 hours max.) or permanent light "OFF". A red light-emitting diode indicates the function selected.



HF-Sensor

Coverage angle

HF 360 AP

Prod. No. grey	751210
Dimensions (h x w x d)	82 x 72 x 64 mm
Output	1000 W max. (e. g. filament bulbs) 500 VA max. (e. g. fluorescent lamps)
Voltage	230 – 240 V / 50 Hz 3-wire connection (L,L',N) parallel connection possible
Angle of coverage	360° with 140° angle of aperture
Reach	1 – 8 m max., infinitely variable
Twilight setting	2 – 2000 lux
Time setting	10 sec. – 30 min.
Manual override	4 hrs. selectable
Permanently OFF	selectable
LED	yes, manual override, permanently
Enclosure	IP 54
Protection class	II
	Subject to technical modifications