

## IR 180 AP




**Sturdy, tried and proven, long-reach sensor switch using infrared technology. In the concealed version, ideal for corridors, kitchens and guest WC's, in the surface-mounted version for basements, garages, carports and outside areas.**

The SensorSwitch responds to the heat radiated from moving persons. With a reach of 8 m, it makes the ideal choice even for large rooms. The IR 180 AP splashproof surface-mounted version with IP 54 enclosure protection rating is also suitable for installation outdoors or in rooms exposed to moisture.

- Splashproof , surface mounted infrared sensor, ideal for basements, garages, carports and outdoor areas

### Settings

- Control dials for easy adjustment of light "ON" time and twilight threshold are protected from accidental maladjustment behind the fold-down trim panel.
- Integrated pushbutton for switching to permanent light "ON" (4 hours max.) or permanent light "OFF". A red light-emitting diode indicates the function selected.



IR sensor

180° angle of Coverage

## IR 180 AP

Prod. No.	<b>750213</b>
Dimensions (h x w x d)	82 x 72 x 66 mm
Output	1000 W max. (e. g. filament bulbs) 500 VA max. (e. b. fluorescent lamps)
Voltage	230 – 240 V / 50 Hz 3-wire connection (L,L',N) parallel connection possible
Angle of coverage	180° with 90° angle of aperture
Reach	8 m max.
Twilight setting	2 – 2000 lux
Time setting	10 sec. – 30 min.
Manual override	4 hrs. selectable
Permanently OFF	selectable
LED	yes, manual override, permanently "OFF"
Enclosure	IP 54
Protection class	II
	Subject to technical modifications