

RS 13 L



Stylish looks in a wide diameter, ideal for corridors, hallways or stairwells.

These lights cut a great figure wherever they are installed – whether on the ceiling or on the wall. The hand-blown opal glass shades are set in a matt-finished crystal glass ring and come in two sizes.

This is how they work

- Invisibly concealed inside, cutting-edge high-frequency sensor technology responds to the slightest movement irrespective of temperature, instantly switching the light "ON" and, after a programmable time, "OFF" again.

Settings

- Infinitely variable, electronic reach adjustment from 1 – 8 meters in diameter.
- Control dials for easy adjustment of light 'on' duration and twilight threshold.

Installation advantages

- Straightforward installation (light and sensor = 1 connection)
- Facility for connecting additional loads (e.g. bathroom/WC extractor fan)
- Bulb can be changed without the need for tools as the glass shade is held in place by a screwless bayonet fitting.

Material

- Three retaining clips for a striking look
- Domed opal glass shade, matt or glossy with speckles
- Base in high-quality, silver-lacquered die-cast aluminum

Main features of SensorLights



Easily mounted to walls or ceilings



Twilight setting





Time setting



Reach setting

Detection zone for wall and ceiling mounting



The 360° detection zone with an aperture angle of 160° and reach of up to 8 m reliably watches over rooms as large as 50 m².

RS 13 L

Prod. No. **white**

730819

Dimensions (h x w x d)

340 mm dia. x110mm

Output

75 W max. / E 27 + 800 W max. / e.g. bathroom/WC extractor fan

Transmission power

approx. 1 mW

HF system

5.8 GHz

Voltage

230 – 240 V/50 Hz

Angle of coverage

360° with 160° aperture angle, also through glass, wood and stud walls

Reach

1 – 8 m dia., infinitely variable

Twilight setting

2 – 2000 lux

Time setting

5 sec. – 15 min.

Enclosure

IP 44

Protection class

II

Subject to technical modifications