

RS 16-2 L / RS 16-3 L



RS 16-2 L white 738211



RS 16-3 L stainless. steel look 738419



RS 16-3 L white 738310

Light that thinks for itself!

Intelligent lights know when to give light and when not. Thanks to modern, invisible high-frequency sensors, these lights respond to the slightest movement. Square, hand-blown, mat opal glass shade. Optionally with trims to suit any taste.

Settings

- Infinitely variable, electronic reach setting from Ø 1 – 8 meters.
- Easy adjustments of light 'ON' duration and twilight threshold by control dial.

Installation advantages

- Easy installation (2 wires ... that's all it takes!).
- Bulb can be changed without the need for tools as screwless glass shade is held in place by bayonet catch.
- The square glass shade can be aligned with ease.

Main features of SensorLights



Easily mounted to walls or ceilings



Twilight setting



Time setting



Reach setting

Technical Data RS 16-2 L / RS 16-3 L

Art.-No.: **RS 16-2 L white 738211**

Art.-No.: **RS 16-3 L stainless. steel look 738419**

Art.-No.: **RS 16-3 L white 738310**

Dimensions (h x w x d)	RS 16-2 L 270 x 270 x 110 mm RS 16-3 L 295 x 295 x 110 mm
Output Additional	60 W max. / E 27 additional switching capacity 100 W max. / e.g. bathroom/WC extractor fan
Voltage	230 – 240 V / 50 Hz
Angle of coverage	360° with 160° aperture angle also through glass, wood and stud walls
Transmitter power	approx. 1 mW
HF system	5.8 GHz
Reach	1 – 8 m dia., infinitely variable 3 – 8 m dia. (RS 16 / 16-2 / 16-3L)
Twilight setting	2 - 2000 lux
Time setting	5 sec. – 15 min.
Enclosure	IP 44
Protection class	II
	Subject to technical modifications