

## IS 360 D TRIO



Prod. No. **black 602512**



Prod. No. **white 602611**

**Infrared ceiling sensor, ideal for uninterrupted, all-round detection under ceilings, porches, carports, soffits or balconies.**

The IS 360 D TRIO is equipped with three highly sensitive infrared detectors positioned at a specific angle in relation to each other to provide reliable, uninterrupted all round protection of areas as large as 350 m<sup>2</sup> beneath it.


### Settings

- Detection zone can be limited by fitting the shrouds supplied.
- Simple adjustments of light ON time and twilight threshold by control dial.

### Installation advantages

- Clearly laid-out terminal compartment for fast, straightforward wiring.


### Main features at a glance



Detection zone



Coverage angle



Multi-lens technology for perfect detection



Coverage angle reduction



Setting functions

### IS 360 D TRIO

(Prod. No. **black 602512**, Prod. No. **white 602611**)

Dimensions (h x w x d)	100 x 120 x 120 mm
Output	1000 W max. (resistive load, e.g. filament bulb) 500 W max. (uncorrected, inductive, $\cos \theta = 0.5$ , e.g. fluorescent lamp) 600 W max. (electronic ballasts, capacitive, e.g. low-energy bulb, 8 each max.)
Voltage	230 – 240 V / 50 Hz
Angle of coverage	360° with 180° angle of aperture
Adjustment range	± 10° precision adjustment of lens
Reach	12 m max. (temperature-stabilized)
Twilight setting	2 – 2000 lux
Time setting	10 sec. – 15 min.
Enclosure	IP 54
Protection class	II
	Subject to technical modifications