

IS -130-2



Prod. No. **white 660314**



Prod. No. **black 660215**

Infrared sensor, ideal for targeting areas in front of buildings, driveways and indoor areas.

The IS 130-2 is the attractively priced gateway to the world of motion-activated switching that offers tried and proven technology for outstanding detection quality in a new design. It reliably watches over areas of up to 150 m².


Settings

- Tilting, turning Fresnel lens for exact adjustment of the detection zone to protection requirements at the site of installation.
- Simple adjustments of light "ON" time and twilight threshold by control dial.

Installation advantages

- Clearly laid-out terminal compartment for fast, straightforward wiring.


Main features at a glance



Detection zone



Coverage angle 130°



Multi-lens technology for perfect detection



90° vertically



50° horizontally

IS 130-2 (Prod. No. **white 660314**, Prod. No. **black 660215**)

Dimensions (hxwxd)	130 x 78 x 84 mm
Output	600 W max. (resistive load, e.g. filament bulb) 500 W max. (uncorrected, inductive, $\cos\theta=0.5$, e. g. fluorescent lamp) 600 W max. (electronic ballasts, capacitive e.g. low-energy bulb, 6 each max.)
Voltage	230 – 240 V / 50 Hz
Angle of coverage	130° with sneak-by guard
Adjustment range	50° horizontally, 90° vertically
Reach	12 m max.
Twilight setting	2 – 2000 lux
Time setting	8 sec. – 35 min.
Enclosure	IP 54
Protection class	II