

IS NM 360



Intelligence and aesthetics perfectly combined.

Outstanding functionality in a unique, new design. There's no better way to describe this visually discreet yet inspiringly different sensor. Its concealed controls permit an almost new kind of functional flexibility. There are 4 sensor and NightMatic combinations to choose from for switching light "ON" and "OFF" just as you please

Settings

- The motion detector's area of coverage can be limited using the shrouds provided.
- Easy, convenient selection of light "ON" time, twilight threshold and programme on removable sensor-module.
- 4 function programmes geared to practical requirements.
-

P 1		Sensor
P 2		Sensor
P 3		Sensor
P 4		Sensor

1. Sensor mode only

2. Approx. 2 h of constant light in the evening – light only comes on after then in response to movement

3. Approx. 2 h of constant light in the evening and morning – light only comes on between then in response to movement

4. Constant light up to midnight – light only comes on after then in response to movement

Main features at a glance



360° angle of Coverage



Perfect coverage with sneak-by guard



Coverage angle reduction



Setting functions



Manual override 2 x OFF/ON

IS NM 360

Prod. No. white

Prod. No. black

Dimensions (h x w x d)

External switching capacity

Voltage

Angle of coverage

Reach

Twilight setting

Time setting

Manual override

Enclosure

Protection class

609313

609214

114 x 100 x 58 mm

1000 W max. (resistive load, e.g. filament bulb)

500 W max. (uncorrected, inductive, $\cos \phi = 0.5$, e.g. fluorescent lamp)

600 W max. (electronic ballasts, capacitive, e.g. low-energy lamp, 8 each max.)

230 – 240 V, 50 Hz

360° with sneak-by guard

8 m all round (mounted at a height of 1.75 – 2 m)

2 - 2000 lux

5 sec. – 15 min.

selectable 4 h

IP 54

II

Subject to technical modifications