

L 726 S



Prod. No. **black 653613**



Prod. No. **white 653712**

The 706-Series lights support their glass shades from above and shine light down.

The 706-Series features the same technology as the 705-Series. Many customers prefer this design of light because it directs light onto steps, perfectly illuminating keyholes etc.

Boasting a 4-segment sensor system and mirror optics for a long focal length, the sensor provides unprecedentedly even, high resolution 360° all-round coverage in a radius of 8 m.

- Hand-blown opal glass shade, polished finish

This is how it works

- Four function programmes geared to practical needs with soft light start as well as 25% basic brightness (Wattomatic) leave you wanting for nothing.
- Manual override (4h) at power switch.

Settings

- Detection zone can be limited by fitting the shrouds supplied.
- Easy, convenient adjustment of light 'on' time, twilight threshold and programme selection on removable sensor module.



Main features at a glance



360° angle of coverage



Perfect coverage with sneak-by guard



Coverage angle reduction



Setting functions



Soft light start



Manual override 2 x OFF/ON

L 726 S

(Prod. No. **black 653613**, Prod. No. **white 653712**)

Dimensions (h x w x d)	285 x 191 x 276 mm
Output / light bulb	100 W max. / E 27 (also suitable for low-energy bulbs)
Voltage	230 – 240 V / 50 Hz
Angle of coverage	360° with sneak-by guard
Reach	8 m all round
Twilight setting	2 – 2000 lux
Time setting	5 sec. – 15 min.
Brightness control	0% or 25% (Watt-o-matic)
Manual override	4 hrs. selectable
Enclosure	IP 44
Protection class	I
	Subject to technical modifications