

L 260 S



Exquisite lights in a modern, sleek look, made of stainless steel and hand-blown opal glass to give bright, even illumination. Ideal as wall, free-standing or bollard lights for gardens, drives or pathways.

The integrated soft-start feature is kind on the eyes and prolongs the life of the bulbs by gradually increasing brightness to full output over a period of 1 second. The electronics are equally as gentle on the light when it is switched off. The built-in infrared sensor technology is economical and easy to use. Manual override at power switch allows you to set the light to stay "ON" for up to four hours.

Settings

- Detection zone can be limited by fitting the shrouds supplied.
- Simple adjustments of light ON time twilight threshold by control dial.

The G 9 adapter modules, exclusively from STEINEL!

In order to achieve a long and evenly illuminated glass shade, these SensorLights are supplied with the innovative G9 modules - a real world first - including halogen lamps.



Main features of L 260 S



Detection zone



Setting function



Reducing reach



Coverage angle Reduction



Soft light start



Manual override 2 x OFF/ON

L 260 S

Prod. No. **stainless steel**

Dimensions (h x w x d)
Angle of coverage
Lamp Adapter
Reach
Output

Voltage
Twilight setting
Time setting
Manual override
Enclosure
Protection class

647315

426 x Ø 102 x 177 mm
240° with 180° angle of aperture including for 2 x 40 W / G9
12 m max. (temperature-stabilized)
2 x or 3 x 40 W max. / G 9 or 100 W max. / E 27
230 – 240 V / 50 Hz
2 – 2000 lux
5 sec. – 15 min.
4 hrs. selectable
IP 44
I
Subject to technical modifications

