

L 270 S



SensorLight with LED back-lit glass panel

Featuring a high-quality aluminum body and cutting-edge STEINEL MiniSensor technology, you can't help but be impressed by the perfect marriage of design and function of the 270-Series.

The attractive highlight of the L 270 S is the flat glass panel illuminated by LED's.

Matching the L 270 S house number light, wall light L 271 S gives a matching look to entrances and the front of buildings.

This is how it works

- LED back-lit house number at dusk, night and dawn.
- Extremely long LED life
- Low energy consumption by LED's
- To illuminate the glass shade evenly, this SensorLight comes complete with two G9 halogen lamps.
- Four function programmes geared to practical needs with soft light start as well as 25% basic brightness (Watt-omatic) leave you wanting for nothing.
- Manual override (4h) at power switch.

Settings

- Detection zone can be limited by fitting the shrouds supplied.
- Easy, convenient adjustment of light "ON" time, twilight threshold and programme selection on removable sensor module.

Installation advantages

- Illuminated panel can be fitted on the left or right depending on whether the light is installed to the left or to the right of the front door.
- Complete with self-adhesive numbers.

Main features at a glance



360° angle of coverage



Perfect coverage with sneak-by guard



Coverage angle reduction



Setting functions



Soft light start



Manual override 2 x OFF/ON

L 270 S

Aluminum	Prod. No.	647810
Dimensions (h x w x d)		270 x 328 x 141 mm
Output / light bulb		2 x 40 W max. / G 9 LED back-lit glass panel, approx. 1 W
Voltage		230 – 240 V / 50 Hz
Angle of coverage		360° with sneak-by guard
Reach		8 m all round
Twilight setting		2 – 2000 lux
Time setting		5 sec. – 15 min.
Brightness control		0% or 25% (Watt-o-matic)
Manual override		4 hrs. selectable
Enclosure		IP 44
Protection class		I
		Subject to technical modifications