

## HS 300 DUO



Prod. No. **black 633219**



Prod. No. **white 633318**


**STEINEL sensor-switched halogen floodlights are the ideal solution when it comes to illuminating the front of buildings, driveways and vulnerable spots with particularly bright light.**

The vigilant floodlights are factory-fitted with bulbs of different ratings ranging from 150 to 500 watts. This automatically picks out special features, welcomes guests and frightens off unwanted visitors. Ranging from the low-price Fresnel lens light HS 5140 to the microprocessor controlled hi-tech floodlight HS 500, the STEINEL line-up offers just the right model for any application. Models HS 150 and HS 300 are equipped with a ceramic reflector.

### Settings

- The detection zone can be adjusted exactly to requirements at the site of installation by means of the tilting, swiveling multilens (HS 150 DUO, HS 300 DUO, HS 500 DUO) or Fresnel lens (HS 5140) and can be limited using the shrouds provided.
- Control dial for easy adjustment of light "ON" duration and twilight threshold.

### HS 300 DUO



Detection zone



Coverage angle reduction



Pull off decorative ring



Twilight, time setting



### HS 150/300/500

The halogen floodlight housing can be tilted from +110° to -40° and swiveled through ±40°. This permits optimum illumination even in situations where installation is awkward

### HS 300 DUO

(Prod. No. **black 633219**, Prod. No. **white 633318**)

Dimensions (h x w x d)	240 x 210 x 180 mm
Output	300 W/R7s max.
Voltage	230 – 240 V / 50 Hz
Angle of coverage	240° with 180° angle of aperture
Adjustment range	80° horizontally, 150° vertically
Reach	12 m max. (temperature-stabilized)
Twilight setting	2 – 2000 lux
Time setting	10 sec. – 15 min.
Enclosure	IP 44
Protection class	I
Lamp	Including 300 W bulb (R7S halogen bulb)
Optional accessories	—



Subject to technical modifications