

AL 602 S



Prod. No. **black 617219**



Prod. No. **white 617318**

Elegant, old-fashioned style sensor lights in die-cast aluminum. Ideal as wall, freestanding or bollard lights for gardens, driveways or pathways.

Their stylish, elegant design is just as reminiscent of the good old days as the hand-blown crystal shade and use of high-quality material: these lights are crafted from highly resistant, coated die-cast aluminum. The electronics are anything but old-fashioned.


Settings

- The detection zone can be adjusted exactly to protection requirements at the site of installation by means of tilting, turning lenses and can also be limited using the shrouds provided.
- Exact time and twilight settings by means of control dial.
- Permanent operation with adjustable basic brightness (Watt-o-matic)
- Multi-lens technology for large detection zone

Watt-o-matic

Permanent lighting can be provided at night thanks to a basic brightness that can be set to any level between 0 and 50%. The light switches to full brightness as soon as someone enters the detection zone.

AL 602 S



Detection zone



Swivel adjustment



Coverage angle reduction



Setting function

AL 602 S

(Prod. No. **black 617219**, Prod. No. **white 617318**)

| | |
|------------------------|---|
| Dimensions (h x w x d) | 480 x 210 x 395 mm |
| Output | 100 W max. / E 27 (no low-energy bulb) |
| Voltage | 230 – 240 V / 50 Hz |
| Angle of coverage | 360° with 120° angle of aperture |
| Adjustment range | 45° horizontally, 40° vertically |
| Reach | 12 m max. |
| Twilight setting | 2 – 2000 lux |
| Time setting | 10 sec. – 15 min. |
| Brightness control | 0 – 50 % (Watt-o-matic) |
| Enclosure | IP 44 |
| Protection class | I |
| Optional accessories | – |
| | Subject to technical modifications |