


HF 3360



Professional sensor in innovative high-frequency design for perfect surveillance of indoor areas

The HF 3360 is a motion detector that works on the basis of cutting-edge HF sensor technology. It emits a 5.8 GHz signal and responds to changes in the echo pattern caused by even smallest movement of persons or objects (e.g. at a distance of 3 m). The HF 3360 responds more or less instantly to any movement in the detection zone, regardless of temperature and walking direction. This makes it the ideal choice for use in stairwells or other indoor spaces. Bristling with electronics, it is designed for professional use. It has a switching capacity of 2000 watts. Sensors connected in parallel are identified automatically. At a reach of up to 8 m, it has a 360° detection zone with an aperture angle of no less than 140°. This makes it possible to watch over large indoor spaces reliably and without the need for major installation work.

- High-frequency wall and ceiling sensor for the perfect surveillance of indoor spaces, detection independent of temperature
- Reach 1 – 8m
- Coverage angle: 360°, angle of aperture: 140°



Installation advantage



Setting capabilities



Prod. No. **753016**

Dimensions (h x w x d)	95 x 95 x 57 mm
Output	2000 W max. (resistive load) 1000 W max. (uncorrected, inductive, $\cos \varphi = 0.5$, e.g. fluorescent lamps) 1800 W max. (series-corrected) 500 W max. (parallel-corrected, at $C = 45.6 \text{ F}$) 1000 W max. (electronic ballasts, capacitive, e.g. low-energy bulbs, 12 each max.)
Voltage	230 – 240 V / 50 Hz (2.5 mm ² max.)
Angle of coverage	360° with 140° angle of aperture, even through glass, wood and stud walls
Reach	8 m max., infinitely adjustable
Sensor system	High-frequency 5.8 GHz Transmission power approx. 1 mW
Time setting	5 sec. – 15 min.
Twilight setting	2 – 2000 lux
Permanent light	selectable
Enclosure	IP 54
Protection class	II
Special features	Including overload protection, identification of parallel-connected sensors, reset function
Accessories (optional)	-BUS system/floating contact as option -Corner wall mount for fitting on internal and external corners
Prod. No.	648114 (white) Subject to technical modifications