

L 890 pure



Add design highlights to any building

The slimline wall lights with different designer-style trims in glass and metal lend an exquisite touch to any building. With four versions available, combining high-quality surfaces with uncompromising STEINEL multisensor technology is a sheer pleasure.

This is how they work:

- Integrated soft light start
- Basic brightness can be adjusted from 0 – 50% (Watt-o-matic). When movement is detected, the light switches to full power for the time selected
- Manual override (4 hrs.) via mains switch


Settings:

- Basic reach can be set to a maximum of 12 m or 5 m by turning the multi-lens
- Detection zone can be limited by fitting the shrouds supplied
- Comfort function buttons for accurately setting light 'ON' duration, twilight threshold as well as for controlling brightness



Detection zone

Setting capabilities



Technical Data L 890 pure

Prod. No. **glass-white**
 Prod. No. **glass-silver**
 Prod. No. **glass-black**
 Prod. No. **alu-silver**
 Prod. No. **alu-anthracite**
 Dimensions (h x w x d)
 Voltage
 Output
 Angle of coverage
 Reach

L 890 pure 656614

L 890 pure 656713

L 890 pure 656812

L 890 pure 656515

L 890 pure 656416

300 x 210 x 120 mm

230 - 240 V / 50 Hz

100 W max. / E 27 (now low energy bulb)

140° with 90° angle of aperture

basic setting 1: 12 m max.

basic setting 2: 5 m max.

temperature-stabilised

10 detection levels (12 m) 9 detection levels (5 m)

480 switching zones (12 m) 412 switching zones (5 m)

5 sec. – 15 min.

2 – 2000 lux

IP 43

II

0 - 50 % (Watt-o-matic)

selectable (4 h)

including soft light start

Subject to technical modifications



Sensor system

Time setting

Twilight setting

Enclosure type

Protection class

Brightness control

Permanent light

Special features