

XLed-FE 25



Prod. No. **black 705817**



Prod. No. **white 705916**

LED Floodlight with Wireless Receiver

- XLed floodlights wirelessly interconnect able in the Impulser system
- LED light head in flat design
- Tilting/turning reflector
- Integrated electronic ballasts
- Active-Thermo-Control



XLed 25

Prod. No.	black 705817
Prod. No.	white 705916
Dimensions (h x w x d)	305 x 200 x 200 mm
Voltage	230 – 240 V, 50 Hz
Output	25 LEDs, approx. 60 W
Enclosure	IP 44
Life of LEDs:	up to 50,000 hours (at 3 hours/day, approx. 45 years)
Switching capacity	- 800 W max. (resistive load, e.g. filament bulb) - 400 W max. (uncorrected, inductive, $\cos \theta = 0.5$, e.g. fluorescent lamps) - 400 W max. (electronic ballasts, capacitive, e.g. low-energy bulbs, 4 each max.)
Operating frequency	868,3 MHz (ISM band)
Programming	at the press of a button / capability of programming up to 8 different transmitters
Special features	Housing tilts through: 200° Housing swivels through: 270°
Accessories	Ground spike silver 365 x 136 x 80 mm Prod. No.: 654917



Subject to technical modifications