

IS-FS 300



IS-FS 300

300° wireless motion detector for wall and corner mounting

- Coverage angle: 300°
- Detects any movement within an area of approx. 300 m², relaying it by radio signal to any STEINEL receiver
- Power supply: 9-V battery (not included)



Technical Data IS-FS 300

Prod.-No.:	black 704711
Prod.-No.:	white 705213
Dimensions (h x w x d)	85 x 60 x 95 mm
Operating voltage / mains connection	9 V block battery* (alkaline) (min. life 12 months.)**
Detection reach	12 m max., electrically stabilised
Sensor system	10 detection levels, 720 switching zones
Angle of coverage	300° horizontally, 180° vertically
Sensor turning range	± 80°
Transmitter range	up to 100 m with uninterrupted line of vision dia. of 30 m indoors
Time setting	1 min. - 15 min.
Twilight setting	2 – 2000 lux
Enclosure	IP 54
Operating frequency	863,3 MHz (ISM-Band)
Transmitter power	less than 1000 µW
Programming	at 5-way DIP switch 32 possible addresses per channel
Number of receivers	Any
Special features	9 V block battery not included
Accessories	Corner wall mount (EWH 01) available 630119 black, 630218 white

Subject to technical modifications

* at a constant temperature < -20° C we recommend the use of 9-V lithium batteries

** depending on triggering frequency (frequency of motion detection)